15

transmitting a data signal over said allocated traffic channels from said base station to said mobile station;

measuring characteristics of the received data signal at the mobile station in each of said allocated traffic channels; and

controlling the transmission power of a base station on basis of the poorest one of said allocated traffic channels

- **30**. A method according to claim **29**, wherein said mobile telecommunications system is a code division multiple access (CDMA) system, and said traffic channels are CDMA traffic channels.
- 31. A method according to claim 30, wherein said CDMA traffic channels are distinguished from each other by different spreading codes.
- **32.** A method according to claim **30**, wherein said traffic channels are distinguished from each other by different Walsh functions.
 - 33. A mobile telecommunications system, comprising:
 - a plurality of mobile stations;
 - a plurality of base stations; and
 - a high-speed data transmission mode having at least two parallel traffic channels allocated to a respective one of said mobile stations only in a downlink direction for 25 high-speed data transmission between a respective serving one of said base stations and said respective one of said mobile stations, and a single control channel for controlling a transmission power of said respective one of said mobile stations from said respective serving 30 one of said base stations.
- **34**. A system according to claim **33**, wherein said mobile telecommunications system is a code division multiple access (CDMA) system, and said traffic channels are CDMA traffic channels.
- **35**. A system according to claim **34**, wherein said CDMA traffic channels are distinguished from each other by different spreading codes.
- **36**. A system according to claim **34**, wherein said traffic channels are distinguished from each other by different 40 Walsh functions.
- 37. A system according to claim 31, 32, 33 or 34, wherein said at least two parallel traffic channels are allocated for a high-speed data transmission only in one direction from the base station to the mobile station.
 - **38**. A mobile telecommunications system, comprising:
 - a plurality of mobile stations;
 - a plurality of base stations; and
 - a high-speed data transmission mode having at least two parallel downlink traffic channels allocated to a respective one of said mobile stations only in a downlink direction for high-speed data transmission from a respective serving one of said base stations to said respective one of said mobile stations, and a single downlink control channel for controlling of the transmission power of the selected respective one of the mobile stations.
- **39**. A code division multiple access (CDMA) mobile telecommunications system, comprising:
 - a plurality of mobile stations;
 - a plurality of base stations; and

16

- a high-speed data transmission mode having at least two parallel CDMA traffic channels allocated to a respective one of said mobile stations for high-speed data transmission from a respective serving one of said base stations to respective ones of said mobile stations, and a single control channel for controlling a transmission power of said respective one of said mobile stations from said respective serving one of said base stations, said at least two parallel traffic channels being allocated for a high speed data transmission only in the direction from the base station to the mobile station.
- **40**. A method for power control in a code division multiple access (CDMA) mobile telecommunications system, said method comprising:
 - allocating at least two parallel CDMA traffic channels for high-speed data transmission over the radio path in direction from a base station of a fixed radio network to a mobile station;
 - transmitting a data signal over said allocated CDMA traffic channels from said base station to said mobile station;
 - measuring characteristics of the received data signal at the mobile station in each of said allocated CDMA traffic channels; and
- controlling the transmission power of the base station on basis of the poorest one of said allocated CDMA traffic channels.
- **41**. A code division multiple access (CDMA) mobile telecommunications system, comprising:
 - a plurality of mobile stations;
 - a plurality of base stations;
 - a high-speed data transmission mode having at least two parallel CDMA traffic channels allocated to a respective one of said mobile stations for high-speed data transmission between a respective serving one of said base stations and said respective one of said mobile stations; and
 - a single control channel for controlling a transmission power of said respective one of said mobile stations from said respective serving one of said base stations, wherein
 - said at least two parallel traffic channels are allocated for a high-speed data transmission only in one direction from the base station to the mobile station.
- **42**. A code division multiple access (CDMA) mobile telecommunications system, comprising:
 - a plurality of mobile stations;
- a plurality of base stations; and

60

- a high-speed data transmission mode having at least two parallel downlink CDMA traffic channels allocated to a respective one of said mobile stations for high-speed data transmission from a respective serving one of said base stations to a respective serving one of said mobile stations, and a single downlink control channel for controlling of the transmission power of said respective serving one of the mobile stations, wherein
 - said at least two parallel traffic channels are allocated for a high-speed data transmission only in one direction from the base station to the mobile station.

* * * * *